



M-324



M-325



Included

313B



Optional*

313S



M-326



M-327

**All Zone Defense™ components are interchangeable.*

B/W CRT Monitor and IR-Weatherproof Cameras

- Mil - Spec phosphor cathode ray tube (CRT) wider voltage input: DC11-32V
- 3AV inputs (4AV inputs for 7"), 1 AV output
- Mirror and normal switch available
- Day/night brightness
- Rugged, double-sided PCB board for increase anti-vibration protection
- Contrast, brightness and volume adjustment
- On-board speaker
- Auto shift to AV1 on when reversing

Specifications

	M-325	M-324	M-327
Image Device	5.5" B/W CRT	4.5" B/W CRT	7" B/W CRT
TV System	CCIR/EIA	CCIR/EIA	CCIR/EIA
Deflection Angle	70°	90°	90°
Resolution (TV Lines)	600	Horiz.: 600 Field: 400	Horiz.: 600 Field: 400
Input Voltage (VDC)	11-32	11-32	11-32
Output Voltage (VDC)	10	10.2 +/- 20%	10.5V 0.2V
Power Consumption	Max. 1A	<= 11W	Max > 18W
Video input/output	1Vp-p75Ohm	1Vp-p75Ohm	1Vp-p75Ohm
Mechanical vibration	6.8G	6.8G	6.8G
Operating temperature	0°C +60°C	-20°C +60°C	-15°C +60°C

Distributed By
Ramco Engineering Inc.

52965 Frederic Drive • Elkhart, IN 46514 800-321-4819 • (574) 266-1455